

Panasonic KX-UT670 SIP Phone Specifications

Display	
LCD Display	262,000 colors
LCD Size	7 inch touch display
LCD Backlight	15/Auto
HD Video	720p
Install Options	
Desk Mount Tilt	Yes – 2 positions
Wall Mount	KX-A434 (optional)
Power Adaptor	KX-A422 (optional)
Audio Features	
Handset, Speaker, Headset Volume	15 levels
Ringtones	32
Ringer Volume	7 levels + Off
Headset Port	2.5 mm
Electronic Hook Switch Control Port*	3.5 mm
Audio Codec	G.711a-law / G.711 μ -law / G.722 (wideband) / G.729a
HD Voice	Yes
Speaker Phone	Yes (Full Duplex)
Keys	
Programmable Keys	24 (4 pages of 6 keys)
Software Features	
Phone Book (Entries)	Depends on memory
Call Log Entries	100 in + 100 out
Conferencing	3 parties (within terminal – multi-party dependent on server)
XML	From 2Q/2012
Music on Hold	Supplied by Host Service (PBX / SIP Server)
Memory	50 MB
IP Features	
SIP Accounts	6
SIP Compatibility	RFC 3261 Standard SIP Server, Asterisk, Broadsoft, Panasonic SIP PBX
IP Version	IPv4
DHCP Client	Yes
DNS	Yes
HTTP	Yes
HTTPS	Yes
SNTP Client	Yes
VLAN (802.1q)	Yes
QoS (DiffServ)	Yes

Configuration	
Plug & Play Configuration	Server based configuration, TR-069, Panasonic Redirect Server
Manual Configuration	Internal web Configurator, Local (LCD based) network configuration
Interface	
Ethernet Ports	2
Ethernet Interface	10/100/1000 Mbps
PoE (Power over Ethernet)	Yes
Bluetooth	Optional
USB	1 (USB 2.0 Host)
SD Card Slot	SDXC Memory Card / SDHC Memory Card / SD Memory Card
Power Consumption	PoE Standby: 5.2 W (Backlight OFF) Talking: 7.0 W AC Adaptor Standby: 4.6 W (Backlight OFF) Talking: 6.2 W Max PoE: 12.9 W AC Adaptor: 11.5 W
Operating Environment	0 °C - 40 °C (32 °F - 104 °F)
Dimensions (Width x Depth x Height; handset on cradle, stand attached)	High position: 270 mm x 180 mm x 220 mm Low position: 270 mm x 192 mm x 170 mm
Weight (with handset, handset cord and stand)	1300 g

* Plantronics headsets can be used with these units. Not all headsets are guaranteed to operate.